

Aqueous Based 90% Efficiency Concrete Curing Compound

Applied to the surface of freshly laid concrete, SAFECURE SUPER physically 'locks' moisture into freshly cast concrete allowing full hydration of the cement thus allowing the concrete to fully cure. This is achieved by covering the surface of the concrete with a very thin temporary membrane that prevents moisture in the concrete from leaving the surface.

Benefits of using include reduced surface shrinkage and cracking, more durable hard wearing surface and prevention of dusting.

SAFECURE SUPER is also available in a fugitive dye tinted form to assist visual indication during application - SAFECURE SUPER T

<u>Advantages</u>

- Reduces surface shrinkage and cracking by controlling moisture loss from surfaces.
- Increases water resistance.
- Enables cement to hydrate more efficiently.
- WRAS Approved WRAS

- · Prevents dusting.
- · Non-toxic and non flammable.
- Eliminates need for damp hessian, sand or polythene
- · NO VOC

Application

SAFECURE SUPER is spray applied to the surface of newly placed concrete. The concrete should be free from surface water and the nozzle of the spray should be held approx. 450mm from the concrete surface and passed back and forth to ensure complete coverage. The pump pressure should be maintained at a level producing a fine spray. Rate of application will be 160 to 270 ml/m² (4 - 6 m²/ltr).

Touch Dry Time: 2 to 4 hours dependent upon temperature and wind

Hard Dry Time: 18 to 24 hours dependent upon temperature and wind

Coverage

Apply the selected grade by spray at a rate of approximately 4-6 m² per litre, taking care to ensure complete coverage. Immediately after use the spraying equipment should be thoroughly washed out with clean water.

<u>St</u>orage

Keep containers sealed. Store in dry conditions at room temperature and away from direct heat. Protect from frost. When stored correctly in an unopened container, storage stability is 2 years.

Shelf Life

Over 2 years in sealed containers.

Specification

SAFECURE SUPER is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

Health and Safety

Avoid physical contact with material. If contact with skin should occur wash with soap and water. If splashes should affect eyes, bathe immediately with clean water and if discomfort persists seek medical advice.

See separate Safety Data Sheet for further information.

Date of issue 03.07.2014 Tech Data Sheet no. 306 Revision no. v2 Page 1 of 1